



SAFETY DATA SHEET

Valspar Premium v700 Walls & Ceilings Silk Base C

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Valspar Premium v700 Walls & Ceilings Silk Base C

Product number 121.0039753.330, 121.0039753.340, 121.0039753.355, 117.0039753.330, 117.0039753.340, 117.0039753.355

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Water-based paint.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Valspar
220 Wharfedale Road,
Winnersh,
Wokingham,
Berkshire,
RG41 5TP
Tel: 0344 736 9174
Email: customerservice@valsparpaint.co.uk

1.4. Emergency telephone number

Emergency telephone 0344 736 9174
(0800 - 1700 Monday - Sunday)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains 1,2-Benzisothiazol-3(2H)-one. May produce an allergic reaction.

Precautionary statements P102 Keep out of reach of children.

VOC Labelling EU: (cat A/b): 100 g/l (2010). This product contains a maximum VOC content of 15 g/l.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Valspar Premium v700 Walls & Ceilings Silk Base C

Calcium carbonate CAS number: 1317-65-3 EC number: 215-279-6 Substance with National workplace exposure limits.	1-5%
Classification Not Classified	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known. However, this product contains VOCs which may cause a headache.
Ingestion	No specific symptoms known. May cause discomfort if swallowed.
Skin contact	May be slightly irritating to skin.
Eye contact	May be slightly irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Specific treatments	No specific chemical antidote is known to be required after exposure to this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	None known.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours.
---	--

Valspar Premium v700 Walls & Ceilings Silk Base C

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and prolonged skin contact.

6.2. Environmental precautions

Environmental precautions The product is not expected to be hazardous to the environment. However, large or frequent spills may have hazardous effects on the environment. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid contact with skin, eyes and clothing. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin, eyes and clothing. Avoid spilling. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead

Advice on general occupational hygiene Clean equipment and the work area every day. Wash contaminated skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Container must be kept tightly closed when not in use. Protect from freezing and direct sunlight.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Calcium carbonate

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Cellulose

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Short-term exposure limit (15-minute): WEL 20 mg/m³ inhalable dust

Titanium dioxide

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

2-methylpentane-2,4-diol

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³

Short-term exposure limit (15-minute): WEL 25 ppm 123 mg/m³

Valspar Premium v700 Walls & Ceilings Silk Base C

Magnesium carbonate

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Aluminium hydroxide

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³

Amorphous silica

Long-term exposure limit (8-hour TWA): WEL 6 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 2.4 mg/m³ respirable dust

Glycerol

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ mist

propane-1,2-diol

Long-term exposure limit (8-hour TWA): WEL 150 ppm 474 mg/m³ total vapour and particulates

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

1,4-dioxane

Long-term exposure limit (8-hour TWA): WEL 20 ppm 73 mg/m³

Sk

Sodium Hydroxide

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls	Provide adequate ventilation.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	No specific hand protection recommended.
Other skin and body protection	Wear appropriate clothing to prevent skin contamination.
Hygiene measures	Wash contaminated skin thoroughly after handling.
Respiratory protection	Respiratory protection not required. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Various colours.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	Not determined.
Evaporation rate	Not determined.
Flammability (solid, gas)	Not determined.

Valspar Premium v700 Walls & Ceilings Silk Base C

Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	Not determined.
Solubility(ies)	Soluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid freezing. Avoid heat.

10.5. Incompatible materials

Materials to avoid Water-reactive materials. Organic peroxides/hydroperoxides.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Valspar Premium v700 Walls & Ceilings Silk Base C

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity The product is not expected to be hazardous to the environment. However, large or frequent spills may have hazardous effects on the environment.

12.2. Persistence and degradability

Persistence and degradability Not determined.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

Valspar Premium v700 Walls & Ceilings Silk Base C

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Reuse or recycle products wherever possible.

Disposal methods Dispose of contents/container in accordance with national regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012, SI 2012/1715

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to Regulation (EC) 1272/2008 EUH208: Calculation method.

Valspar Premium v700 Walls & Ceilings Silk Base C

Revision comments	Revised formulation.
Revision date	10/07/2017
Revision	3
Supersedes date	19/09/2016
SDS number	1731
Hazard statements in full	EUH208 Contains 1,2-Benzisothiazol-3(2H)-one. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.