

**PRODUCT SUMMARY**

Valspar® Trade Contract Matt is a professional, high opacity emulsion that gives excellent coverage. This formulation has been specially designed with the trade professional in mind, to achieve the perfect finish for your job, efficiently. You can choose a colour and be confident that it will stay true over time. Faster work, better job. Suitable for interior wall and ceiling surfaces.

Available in Pure Brilliant White & Magnolia

**PRODUCT FEATURES & BENEFITS**

- High opacity
- Ideal for new plaster
- Excellent coverage

**RECOMMENDED USES/SUBSTRATES**

- Plasterboard
- Dry wall
- Wallpaper
- New Plaster

When using on new plaster, allow plaster to dry for 1 week before painting.

**APPLICATION**

Application method: Brush, roller or sprayer.  
For indoor use only. Stir well before use to ensure paint is thoroughly mixed. Do not apply in damp or humid conditions.  
Apply when temperature of the surface being painted is above 10°C. When purchasing more than 1 container of the same colour, intermix containers to ensure colour uniformity.

- Do not thin this product.
- Touch dry in 1 hour
- Allow 2–4 hours between coats.

When using a sprayer, make sure you refer to the sprayer user guide for full instructions before use. You can dilute this paint with water, however, when you dilute the formula you dilute the quality. Therefore, we cannot guarantee the claims we make on pack if the formula is diluted with water.

**SURFACE PREPARATION**

For best results, read information below before use:

- New, fresh plaster must be sealed with Valspar® Contract Matt prior to painting.
- Other bare, absorbent surfaces must be sealed with with Valspar® Trade Primer & Undercoat prior to applying the finishing coat. You can dilute this paint with water to use as a first coat on new plaster.
- The surface must be clean, dry and free of dust and grease
  - Glossy surfaces should be deglossed before painting
  - Repair all damaged areas
  - Remove old, loose or flaky paint
  - When making dramatic colour changes or applying bold colours, we recommend using Valspar® Primer & Undercoat prior to applying Valspar® Trade Matt Walls & Ceiling paint.
- Walls and ceilings need to reach a neutral pH (7) before applying product. Do not apply to walls with a pH higher than 8. To check the pH of your wall, apply water to the wall and pH paper.  
Allow at least 1 week for finish to fully harden before washing surfaces with a mild detergent.

**STORAGE & DISPOSAL**

After painting, remove as much paint as possible from paint equipment before cleaning with warm, soapy water.

Please dispose of unused paint responsibly. Check with your local authority to see if they provide facilities for the disposal of waste paint. If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses. Pour the leftover paint into a box with shredded paper or cat litter, allow it to solidify in a well-ventilated area away from children or pets, and then dispose with household rubbish.

Store paint in a dry area and protect from frost.

**HEALTH & SAFETY**

Always read the full Health and Safety Information on can prior to use. VOC content: EU limit for this product (Category A/a): 30 g/l (2010). This product contains a maximum VOC content of 5 g/l.  
VOC Globe category - MINIMAL  
Please contact Valspar Customer Service on 0344 736 9174 or [customerservice@valsparpaint.co.uk](mailto:customerservice@valsparpaint.co.uk) for the safety datasheet, available on request.

**SHIPPING & PACKAGING**

Freight Classification: Paint or Paint Related Material  
Protect from freezing  
Packaging: Case of 1

**FURTHER SUPPORT**

If you require further support, please contact Valspar Customer Service on 0344 736 9174 or [customerservice@valsparpaint.co.uk](mailto:customerservice@valsparpaint.co.uk).  
Always read full Health, Safety & Environmental Information on can before use.  
(UK) Sherwin-Williams UK Limited. Avenue One, Station Lane, Witney, Oxfordshire, OX28 4XR, UK Tel: 0114 240 9469  
(IRL) 644 Jordanstown Road, Aerodrome Business Park, Rathcoole, D24 XE8F Tel: +353 1 2135760

PRODUCT SPECIFICATIONS	
Valspar Trade Contract Matt	
<b>Product type:</b>	Acrylic Water based paint
<b>Viscosity:</b>	95 - 110 KU
<b>Sheen:</b>	Matt: <10 at 85°
<b>VOC (g/l):</b>	2.8599999999999999
<b>Solid content of base (before colourant):</b>	Volume Solids: 34.81% Weight Solids: 43.09%
<b>Coverage:</b>	10 m <sup>2</sup> /L
<b>Recommended film thickness (wet) per coat:</b>	0.10 – 0.15 mm
<b>Recommended film thickness (dry) per coat:</b>	0.08 – 0.12 mm
<b>Touch dry:</b>	1 Hour
<b>Recoat:</b>	2 - 4 Hours
<b>Application Temperature:</b>	10–32°C
<b>Storage temperature:</b>	5–38 deg °C. Do Not Freeze
<b>Testing &amp; Certifications (ISO Ratings):</b>	Wet-scrub resistance: ISO 11998 (Class 5) Stains test: ISO2812-4:2007 Opacity: ISO6504 (99.3) Gloss: ISO2813 Water resistance: ISO2812-4:2007 (1, recovery 4)
<b>Leave 1 week to cure before washing</b>	