

PRODUCT SUMMARY

With even coverage and low-spatter application, it's perfect for fast, stress-free home updates. Choose from a curated palette of Valspar's must-have shades, all with a wipeable finish that resists every day marks and scuffs – so your space stays stylish with minimal effort.

PRODUCT FEATURES & BENEFITS

- Even coverage, flawless finish
- Low spatter, easy to apply
- Wipe clean & durable
- Low odour & water-based

SUSTAINABILITY

- Packaging is made with 40% recycled plastic
- Renewable energy is used in the manufacturing of this product
- 99.9% VOC free for cleaner indoor air quality

RECOMMENDED USES/SUBSTRATES

- Walls
- Ceilings

SHIPPING & PACKAGING

Freight classification: Paint or paint related material. Protect from freezing. Packaging: Case of 1.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EU limit for this product (Cat A/a): 30g/l (2010). This product contains a maximum VOC content <1 g/l. Water-based paint. Ensure good ventilation during drying and application. When applying it is advisable to wear eye protection. Avoid inhalation of dust, wear a face mask when dry sanding.

SURFACE PREPARATION

Always check the health & safety info before you begin. Low odour formula – ideal for indoor spaces. Avoid painting in extreme temperatures and damp or humid conditions – it can affect the final finish. Seal new or bare plaster with this paint thinned by 5% with clean water or use a dedicated bare plaster paint. Clean surfaces thoroughly – remove grease, mould and dust for a dry, sound base. For previously painted surfaces, wash down, sand well and remove any loose or flaking paint. Fill any cracks, dents or holes with a suitable filler. Prime first when painting bold colours or tackling tricky surfaces.

APPLICATION

1. Stir thoroughly before use. Mix tins of the same colour to keep the finish consistent. If you're running low, stop at a corner or natural break.
2. Apply two coats using a quality brush, roller or sprayer. Don't overwork it – avoid excessive brushing or rolling. Bold colour changes may need an extra coat.
3. It will be touch dry in 1 hour and ready for a second coat in 2-4 hours.

STORAGE & DISPOSAL

Wipe up any spills straight away with a damp cloth. Remove as much paint as possible from brushes and rollers before cleaning with warm, soapy water. Do not wash paint down the drain when cleaning. If you're unable to reuse or store leftover paint, do not pour down drains or into watercourses. Dispose of unused paint responsibly – check with your local authority for guidance. Store in a cool, dry place and protect from frost.

Please contact Valspar Customer Service for the Safety Datasheet, available on request.



PRODUCT SPECIFICATION

Product type:

Acrylic water-based paint

Viscosity:

105-115 KU

Sheen:

Matt: <10 at 85°

VOC:

Trace

Volume solid content of base:

Volume solids:

Coverage:

14m²/L

Touch dry:

1 hour

Recoat:

2-4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10°C

Storage temperature:

5-38°C – do not freeze

Certifications:



If you require further support, please contact Valspar Customer Service on **0344 736 9174 (UK) / 01 907 5488 (ROI)** or **customerservice@valsparpaint.co.uk**

Sherwin-Williams UK Limited, Avenue One, Station Lane, Witney, Oxfordshire, OX28 4XR, UK
Sherwin-Williams (Ireland) Ltd, Registered in Ireland 088980, Unit 53, Robinhood Industrial Estate, Dublin 22, D22 PW99

SHERWIN WILLIAMS