

PRODUCT SUMMARY

Valspar® Trade Tough Eggshell is a superior emulsion. Its advanced water-based technology is quick drying and low spatter, making it both easy to use and to clean up. Valspar® Trade Tough Eggshell is stain resistant and scrubbable, giving long-term performance and preventing stains from setting into the surface. Suitable for high traffic areas, making it the perfect choice for a space used daily. With its high opacity and superior covering power, it ensures excellent application. Valspar® Trade - formulated for the perfect finish.

PRODUCT FEATURES & BENEFITS

- Tough for high traffic areas
- Mould and moisture protection
- Excellent stain protection
- Suitable for walls, ceilings wood and radiators

RECOMMENDED USES/SUBSTRATES

- Walls
- Ceilings
- Kitchens
- Bathrooms
- Wood
- Radiators

SPRAYER GUIDE

Application method: Brush, roller or sprayer

Sprayer	Airless SF 23 Pro
Gun	Vector Pro
Tip Type	HEA ProTip
Tip Size	517
Dilution	0%
Spraying Pressure	1800 psi

*Derived from usage patterns of Wagner sprayers

SHIPPING & PACKAGING

Freight classification: Paint or paint related material.

Protect from freezing.

Packaging: Case of 1

SHERWIN-WILLIAMS

SURFACE PREPARATION

Read health and safety information before painting. For indoor use only; do not apply in damp or humid conditions. Remove grease, mould and dust completely for a clean & dry surface. New plaster and other bare, absorbent surfaces must be sealed. For previously painted surfaces, wash, sand, and remove loose or flaky paint. Sand the surface before painting. Fill cracks, dents, or holes with a suitable filler. Use a suitable primer when making bold colour changes or when painting difficult surfaces

APPLICATION

Stir paint thoroughly. Mix containers of the same colour for uniformity. Stop at a corner or natural break if running out of paint. Apply 2 coats using a suitable brush, roller, or sprayer. Avoid excessive rolling or brushing. Apply liberally, working from dry areas into the wet edge. Extra coats may be needed for dramatic colour changes. To use as a mist coat, dilute with 20% water. When you dilute the paint, you dilute the quality. Dries to the touch in approximately 1 hour. Wait 2-4 hours before applying the next coat. Allow 28 days to cure for ultimate durability.

STORAGE & DISPOSAL

CLEANING UP: Wipe up any spills straight away with a damp cloth. Remove as much paint as possible from brushes and rollers before cleaning with warm soapy water. Do not wash paint down the drain when cleaning brushes and rollers.

STORAGE & DISPOSAL: Dispose of unused paint responsibly – check with your local authority for guidance. Do not empty any leftover paint into drains or watercourses. Store in a cool, dry place and protect from frost.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Water-based paint. Ensure good ventilation during application and drying. When applying, it is advisable to wear eye protection. Special precautions should be taken during surface preparation of pre-1990s paint surfaces over wood and metal as they may contain harmful lead. Avoid inhalation of dust. Wear a face mask if dry sanding. EU limit for this product (Cat A/b): 100g/l (2010). This product contains max 1 g/l VOC. Contains a biocidal product for protection of the dried paint film against mould growth: IPBC.

PRODUCT SPECIFICATION

Product Type:

Acrylic water-based paint

Viscosity:

100 – 115 KU

Sheen:

10 – 20 (60°)

VOC:

Trace

Volume Solid Content:

33% - 35%

Coverage:

17m²/L

Touch dry:

1 hour

Recoat:

2 - 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10.

Storage temperature:

Avoid extreme temperatures – do not freeze.

Certifications:



If you require further support, please contact Valspar Customer Service on **0344 736 9174 (UK) / 35319075488 (ROI)** or **customerservice@valsparpaint.co.uk**

Sherwin-Williams UK Limited, Avenue One, Station Lane, Witney, Oxfordshire, OX28 4XR, UK

Sherwin-Williams (Ireland) Ltd, Registered in Ireland 088980, Unit 53, Robinhood Industrial Estate, Dublin 22, D22 PW99